

Stock No. 01321-02-xxxx

ND	Stock No.	L Movements		Springrate		Weight	Flange dimensions						
		Neutral	ΔAx.	ΔLat.	Ax.	Lat.		Outer dia (Ød)	Inner dia (ID)	PCD	Holes	Т	Flange
		[mm]	+/- [mm]	+/- [mm]	[N/mm]	[N/mm]	[kg]	[mm]	[mm]	[mm]	Nxø	[mm]	standard
100	01321-02-0100	400	50	30	30	10	8,5	220	115,5	180	8xø18	10	DIN 2576
125	01321-02-0125	400	50	30	30	10	11,0	250	141,5	210	8xø18	10	DIN 2576
150	01321-02-0150	400	50	30	30	10	12,5	285	170,5	240	8xø22	10	DIN 2576
200	01321-02-0200	400	50	30	30	10	12,5	340	221,5	295	8xø22	10	DIN 2576
250	01321-02-0250	400	50	30	30	10	15,2	375	276	335	12xø18	16	DIN 86044
300	01321-02-0300	400	50	30	50	50	19,8	440	327	395	12xø22	16	DIN 86044
350	01321-02-0350	400	50	30	50	50	25,0	490	359	445	12xø22	16	DIN 86044
400	01321-02-0400	400	50	30	50	50	27,6	540	410	495	16xø22	16	DIN 86044
450	01321-02-0450	400	50	30	50	50	32,0	595	461	550	16xø22	16	DIN 86044
500	01321-02-0500	500	75	20	50	50	38,9	645	512	600	20xø22	16	DIN 86044
550	01321-02-0550	500	75	20	50	50	53,0	703	563	650	20xø22	20	DIN 86044

Pipeconnect

Exhaust gas expansion joint for turbo charger outlet.

Multi-ply bellow with loose flanges.

Stock no. 01300

Description:

Expansion joint for turbo charger outlet with multi-ply, double bellow design with loose (turnable flanges. See also

Technical information Mountting instruction

Material:

• Welding ends: S235JRG2

Bellow: EN 1.4541

Surfuce treatment:

 Flanges are protected with oil

